



# 1/8" One Way Shut-Off 2 Series

See Specifications & Performance Data on Page 8.

## PLUGS



## SOCKETS



MANUAL

### FEATURES

- High flow capability for small coupler
- Only 5/8" diameter
- Socket weighs 1 oz.
- Precision leak-proof seal
- Positive locking mechanism

### CAT. NO.

### CAT. NO.

### FEMALE THREAD

1/8 FPT	23-2	
1/4 FPT	27-2	

2302 ●	
2702	

### MALE THREAD

1/8 MPT	22-2 ■ ●	
1/4 MPT	24-2	

2202 ●	
2402	

### HOSE STEM (Require Hose Clamps)

1/8 I.D.	02-2	
3/16 I.D.	03-2	
1/4 I.D.	04-2	

2022	
2032	
2042	

### SELF STORING AIR HOSE

1/4 I.D.	1502	
----------	------	--

### REUSABLE HOSE CLAMP

ID	OD		SAA-2 SAO-2
3/16 x 3/8			
3/16 x 7/16			
1/4 x 1/2	PB3-2		SAA-2 SAO-2
1/4 x 9/16	PB5-2		
1/4 x 5/8	PB7-2		
1/4 x 11/16	PB9-2		

### PLASTIC & METAL TUBING

.170 x 1/4 Plastic	PJ8-2		SJ8-2 SJ8-2M
1/4 Soft Metal	PJ8-2M		

### PANEL MOUNT (Max. Panel Thickness 3/4")

.170 x 1/4 Plastic	SJ8P-2
1/4 Soft Metal	SJ8P-2M



### VALVE CORE (Brass)

.170 x 1/4 Plastic	PJ8-2V
1/4 Soft Metal	PJ8-2VM



- Available In Brass – Suffix B
- Available In 303 Stainless – Suffix S/S